





- ① REFERENCE APPLICATION SPEC 114-13059 FOR RECOMMENDED PLATED THRU HOLE DIAMETER AND PLATING THICKNESSES.
- ② MATERIAL:
CONTACT AND SHIELD - PHOSPHOR BRONZE
HOUSING - GLASS FILLED POLYESTER. UL 94V-0.
- ③ FINISH: SIGNAL AND GROUND CONTACTS:
MATING AREA: MEETS THE PERFORMANCE REQUIREMENTS OF PRODUCT SPECIFICATION 108-2055; BASED ON TELCORDIA GR-1217-CORE, APPLICATIONS IN UNCONTROLLED ENVIRONMENTS
COMPLIANT PIN AREA: 0.5µm MIN BRIGHT TIN-LEAD OVER BASE PLATING
- ④ CONNECTOR MARKED WITH PART NUMBER AND DATE CODE.
- ⑤ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- ⑥ THE TWO GROUNDS IN EACH COLUMN ARE COMMONED.

7. CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE:
GR-1217-CORE, ISSUE 1, NOVEMBER 1995.

3.80	1469076-2
5.30	1469076-1
DIM M	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG S. J. MAGARO 28SEP01 CHK N. SCHROLL 28SEP01 APVD R. PATTERSON 16AUG2007		 TE Connectivity	
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±.0 1 PLC ±.01 2 PLC ±.02 3 PLC ±.05 4 PLC ±.1 ANGLES ±.5°		NAME HEADER ASSEMBLY, 2 PAIR, 1.8mm TAIL, 25mm, HMZd	
MATERIAL 		FINISH 		SIZE A1	
		WEIGHT -		CAGE CODE 100779	
		CUSTOMER DRAWING -		DRAWING NO C=1469076	
				SCALE 8:1	
				SHEET 1 OF 1	
				REV C	